


**INSTRUMENT
APPROACH
CHART - ICAO**

TRANSITION ALTITUDE
10 000 ft
AD ELEV 436 - 16 hPa
THR RWY 31 ELEV 433,7 - 16 hPa

ŠTEFÁNIK RADAR 134,925 (118,975)
ŠTEFÁNIK TOWER 118,300 (118,700)
ŠTEFÁNIK ATIS ARRIVAL 133,880

**BRATISLAVA/M. R. Štefánik (LZIB)
ILS CAT II & III A RWY 31
ACFT CAT A/B/C/D**




MISSED APPROACH

Climb to TP (1,5 DME OB), turn RIGHT to VOR JAN climbing to 3000 AMSL. MAX IAS 185 kt until established on track to VOR JAN.

ALTERNATE MISSED APPROACH IN CASE OF DME OB UNSERVICEABLE

Climb STRAIGHT AHEAD, at 800 AMSL turn RIGHT to VOR JAN climbing to 3000 AMSL. MAX IAS 185 kt until established on track to VOR JAN. No turn before MM (L B).

THR RWY 31 ELEV 433,7 - 16 hPa
NM to/from THR RWY 31



OCA (OCH)		A	B	C	D
Straight - in Approach	CAT II	ft 588 (154)	605 (171)	617 (183)	631 (197)
	CAT III A	approved			

DME OB	NM	6,0	5,0	4,0	3,0	2,0
ALTITUDES	ft	2370	2042	1716	1391	1069

Ground speed	kt	70	90	100	120	140	160	180
Rate of descent (3,0°)	ft/min	372	478	531	637	743	849	955

CHANGES: DME OB distance on MM BARKA changed; Štefánik CTR, Bratislava TMA redesigned